What is claimed is:

1)   A wireless handheld device, comprising:

a processor; and,

5   a memory, coupled to the processor, capable to store a software component for simultaneously attaching a short distance wireless network to a wide area network having a first address providing a first service and a second address providing a second service.

2)   The device of claim 1, wherein the first and second addresses identify a

10   domain providing respective predetermined privileges.

3)   The device of claim 1, wherein the first and second addresses are access point names ("APNs").

15   4)   The device of claim 1, wherein the first and second addresses include a first and second port number.

5)   The device of claim 1, wherein the first service provides a wireless application protocol ("WAP")

20

6)   The device of claim 1, wherein the first service provides access to the Internet.

7)   The device of claim 1, wherein the first service provides a hypertext

25   transfer ("HTTP") protocol.

8)   The device of claim 1, wherein the first service is a multimedia messaging Service Center ("MMSC").

9)   The device of claim 1, wherein the selectively attaching includes establishing a dial-up network session.

10)   The device of claim 1, wherein the selectively attaching includes establishing a short-range LAN access profile session.

11)   The device of claim 1, wherein the software component selectively attaches response to a first terminal in the short distance wireless network communicating with the device.

12)   The device of claim 11, wherein the communicating includes the terminal transmitting an IP message including a port number.

13)   The device of claim 1, wherein the wide area network is a Global System for Mobile communications ("GSM") cellular network.

14)   The device of claim 1, wherein the short distance wireless network is a Bluetooth™ wireless local area network.

15)   The device of claim 1, wherein the device further includes a short-range LAN Access profile software component.

16)   The device of claim 3, wherein the software component further includes a table of available APNs.

17)   A method for communicating with a cellular network, comprising the steps of:

generating a first short-range radio message including a first IP address and a first port number for the cellular network, by a terminal, in a short distance wireless network;

receiving, by a device, the first short-range radio message;

determining whether the device is attached to the first port number;

generating a cellular signal, by the device, requesting a first service from the cellular network responsive to the first short-range radio message;

5   generating a second short-range radio message including a second IP address and a second port number for the cellular network, by a terminal, in a short distance wireless network;

receiving, by a device, the second short-range radio message;

determining whether the device is attached to the second port number; and,

10   generating a cellular signal, by the device, requesting a second service from the cellular network responsive to the second short-range radio message.

18)   The method of claim 17, wherein the terminal is a messaging terminal and the device is a cellular telephone.

15

19)   The method of claim 14, wherein the cellular network is a Global System for Mobile communications ("GSM") cellular network and the first service is a WAP service and the second service is Internet access.

20   20)   The method of claim 14, wherein the short distance wireless network is a Bluetooth™ wireless local area network.

21)   The method of claim 14, wherein the short distance wireless network is an 802.11 wireless local area network.

25

22)   A method for communicating with a cellular network, comprising the steps of:

receiving, by a device, a plurality of short-range radio messages, from a respective plurality of terminals, in a short distance wireless network for a plurality of respective services in the cellular network; and,

attaching simultaneously to the respective services, by the device, responsive to the plurality of requests.

23) An system for providing communication between a cellular network and a short distance wireless network, comprising:

a hand-held wireless device, including:

a cellular transceiver to communicate with the cellular network;

a short-range transceiver to communicate with the short-range radio network, including to receive a first short-range radio message having a first APN and a second short-range radio message having a second APN;

a memory, coupled to the cellular and short-range radio transceivers, to store a software component to simultaneously transfer a plurality of packets to the first APN and the second APN responsive to the first and second short-range radio messages; and,

a first wireless device to generate the first and second short-range radio messages.

24) The system of claim 23, wherein the first wireless device is selected from a group consisting of a desktop computer, a laptop computer, a personal digital assistant, a headset, a pager, a pen, a printer, a watch, a digital camera and an equivalent.

25) An article of manufacture, including a computer readable medium, comprising:

a short-range radio software component to provide a short-range radio signal in a short distance wireless network;

a cellular software component to provide a communication signal in a cellular network; and,

a software component to simultaneously transfer a plurality of packets between the a first APN and a second APN in the cellular network and the short distance wireless network responsive to a first short-range radio message including a first IP address and fir port number and a second short-range radio message including a second IP address and a second port number.